

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2008

Version No. 1

Revision: 18.08.2008

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** UZIN PE 317
- **Application of the substance / the preparation** Synthetic resin primer
- **Manufacturer/Supplier:**
UZIN Ltd.
7/8 Cholswell Court Shippon
Abingdon, OX 13 6 HW
Tel. 01235/53 41 06
Fax 01235/53 41 07
- **Further information obtainable from:**
Product safety department
email: msds.info@uzin-utz.com
- **Information in case of emergency:**
Medical emergencies: +49 30 30 686 790
Transportation emergencies: +49 621 60 43 333

2 Hazards identification

- **Hazard description:**



Xi Irritant
F Highly flammable

- **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
R 11 Highly flammable.
R 18 In use, may form flammable/explosive vapour-air mixture.
R 36 Irritating to eyes.
R 66 Repeated exposure may cause skin dryness or cracking.
R 67 Vapours may cause drowsiness and dizziness.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4	ethyl acetate	Xi, F; R 11-36-66-67	50-75%
CAS: 67-64-1 EINECS: 200-662-2	acetone	Xi, F; R 11-36-66-67	25-50%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

GB

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2008

Version No. 1

Revision: 18.08.2008

Trade name: UZIN PE 317

(Contd. of page 1)

5 Fire-fighting measures

- **Suitable extinguishing agents:**
CO₂ powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards caused by the substance, its products of combustion or resulting gases:**
Can form explosive gas-air mixtures.
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:**
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
Ensure adequate ventilation
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Immediately remove all soiled and contaminated clothing
Wear suitable protective clothing, gloves and eye/face protection.
Keep away from foodstuffs, beverages and feed.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.
Wash hands before breaks and at the end of work.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm
	Long-term value: 200 ppm

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm

- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2008

Version No. 1

Revision: 18.08.2008

Trade name: UZIN PE 317

(Contd. of page 2)

Wear suitable protective clothing, gloves and eye/face protection.

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

Not necessary in well ventilated areas or areas with local exhaust ventilation (e.g. ex-protected ventilation / evacuation equipment).

In case of prolonged exposition in poorly ventilated areas, e.g. in closed rooms, use ambient air-independent breathing apparatus.

· **Protection of hands:**



Use gloves of stable material (e.g. Nitrile) - if necessary tricoted to improve the wearability.

· **Material of gloves**

Butyl rubber, BR

Nitrile rubber, NBR

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Fluid
Colour:	Red
Odour:	Solvent-like

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** -15°C

· **Ignition temperature:** 460°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.
In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower: 2.1 Vol %

Upper: 13.0 Vol %

· **Vapour pressure at 20°C:** 233 hPa

· **Density at 20°C:** 0.9 g/cm³

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

(Contd. on page 4)

GB

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2008

Version No. 1

Revision: 18.08.2008

Trade name: UZIN PE 317

(Contd. of page 3)

- **Viscosity:**
Kinematic at 20°C: 15 s (DIN 53211/4)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Slightly irritant effect may occur.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

12 Ecological information

- **General notes:** Do not allow product to reach ground water, water course or sewage system.

13 Disposal considerations

- **Product:**
- **Recommendation**
Do not allow product to reach sewage system.
Disposal should be in accordance with local, state or national legislation.
- **Uncleaned packaging:**
- **Recommendation:**
Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 18.08.2008

Version No. 1

Revision: 18.08.2008

Trade name: UZIN PE 317

(Contd. of page 4)

- **Danger code (Kemler):** 33
- **UN-Number:** 1133
- **Packaging group:** II
- **Hazard label** 3
- **Description of goods:** 1133 ADHESIVES, special provision 640D

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1133
- **Label** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** ADHESIVES

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1133
- **Label** 3
- **Packaging group:** II
- **Proper shipping name:** ADHESIVES

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant
F Highly flammable

· **Risk phrases:**

11 Highly flammable.
18 In use, may form flammable/explosive vapour-air mixture.
36 Irritating to eyes.
66 Repeated exposure may cause skin dryness or cracking.
67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

16 Keep away from sources of ignition - No smoking.
23 Do not breathe vapour.
24/25 Avoid contact with skin and eyes.
37 Wear suitable gloves.
51 Use only in well-ventilated areas.

GB

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 18.08.2008

Version No. 1

Revision: 18.08.2008

Trade name: UZIN PE 317

(Contd. of page 5)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

11 Highly flammable.

36 Irritating to eyes.

66 Repeated exposure may cause skin dryness or cracking.

67 Vapours may cause drowsiness and dizziness.

· Department issuing MSDS: Product safety department**· Contact:**

Dr. M. Zieger, phone +49 (0)731 4097 207

E-Mail: msds.info@uzin-utz.com

GB